

Issuing Date 14-Oct-2021  
Revision date 30-Oct-2023  
Revision Number 3

## 1. Identification

**Product Name** ThreeBond 1184E

### Details of the supplier of the safety data sheet

#### **Supplier**

ThreeBond Fine Chemical Co., Ltd.  
1-1 Oyama-cho, Midori-ku, Sagami-hara-shi, Kanagawa 252-0146 Japan

#### **Emergency telephone number**

+81-42-703-7126 (Inquiries regarding SDS content)  
+81-42-670-5333 (Inquiries regarding the product or SDS claim)

### Recommended use of the chemical and restrictions on use

**Recommended use** Adhesive, Sealant

**Restrictions on use** Please be sure to confirm in advance the appropriateness and safety of using the product for the relevant application. If the product is to be used for applications other than those recommended, please seek professional judgment. This product is for industrial use and its use for household and medical implants is prohibited.

## 2. Hazard(s) identification

### GHS Classification

Flammable liquids	Category 3
Acute toxicity - Oral	Category 4
Acute toxicity - Dermal	Category 4
Acute toxicity - Inhalation (Gases)	Classification not applicable
Acute toxicity - Inhalation (Vapors)	Category 3
Acute toxicity - Inhalation (Dusts/Mists)	Category 4
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Respiratory sensitization	Classification not possible
Skin sensitization	Classification not possible
Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 2
Reproductive toxicity	Category 1A
Effects on or via lactation	Yes
Specific target organ toxicity (single exposure)	Category 1, Category 3
Category 1 Central nervous system, kidneys, liver, Respiratory system.	
Category 2 blood system.	
Category 3 Target organ effects: Respiratory irritation, Narcotic effects.	
Specific target organ toxicity (repeated exposure)	Category 1
Category 1 nervous system, Respiratory system.	
Category 2 auditory organs, blood system.	
Aspiration hazard	Category 1

Acute aquatic toxicity	Category 2
Chronic aquatic toxicity	Category 2
Ozone	Classification not possible

**GHS label elements****Signal word**

Danger

**Hazard statements**

H226 - Flammable liquid and vapor  
H302 - Harmful if swallowed  
H312 - Harmful in contact with skin  
H332 - Harmful if inhaled  
H331 - Toxic if inhaled  
H315 - Causes skin irritation  
H319 - Causes serious eye irritation  
H340 - May cause genetic defects  
H351 - Suspected of causing cancer  
H360 - May damage fertility or the unborn child  
H362 - May cause harm to breast-fed children  
H335 - May cause respiratory irritation  
H336 - May cause drowsiness or dizziness  
H411 - Toxic to aquatic life with long lasting effects  
H304 - May be fatal if swallowed and enters airways  
H370 - Causes damage to organs  
H372 - Causes damage to organs through prolonged or repeated exposure  
Causes damage to the following organs: Central nervous system, kidneys, liver, Respiratory system.  
May cause damage to the following organs: blood system.  
Causes damage to the following organs through prolonged or repeated exposure: nervous system, Respiratory system.  
May cause damage to the following organs through prolonged or repeated exposure: auditory organs, blood system.

**Precautionary statements****Prevention**

- Do not handle until all safety precautions have been read and understood
- Wear protective gloves/protective clothing/eye protection/face protection
- Do not breathe dust/fume/gas/mist/vapors/spray
- Avoid contact during pregnancy and while nursing
- Wash face, hands and any exposed skin thoroughly after handling
- Do not eat, drink or smoke when using this product
- Use only outdoors or in a well-ventilated area
- Avoid release to the environment
- Ground and bond container and receiving equipment
- Use non-sparking tools
- Take action to prevent static discharges
- Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
- Keep container tightly closed
- Keep cool
- Obtain special instructions or technical data sheet before use
- Use explosion-proof electrical/ ventilating/ lighting/ equipment

**Response**

- IF exposed or concerned: Get medical advice/attention
- IF exposed or concerned: Call a POISON CENTER or doctor
- Specific treatment (see section 4 on this SDS)

**Eyes**

- Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
- If eye irritation persists: Get medical advice/attention

**Ingestion**

- IF SWALLOWED: Call a POISON CENTER or doctor if you feel unwell
- Rinse mouth
- IF SWALLOWED: Immediately call a POISON CENTER or doctor
- Do NOT induce vomiting

**Skin**

- IF ON SKIN: Wash with plenty of water and soap
- Call a POISON CENTER or doctor if you feel unwell
- Take off contaminated clothing and wash it before reuse
- If skin irritation occurs: Get medical advice/attention
- IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]

**Inhalation**

- IF INHALED: Remove person to fresh air and keep comfortable for breathing
- Call a POISON CENTER or doctor
- Call a POISON CENTER or doctor if you feel unwell

**Fire**

- In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish

**Spill**

- Collect spillage

**Storage**

- Store locked up
- Store in a well-ventilated place. Keep container tightly closed

**Disposal**

- Dispose of contents/container to an approved waste disposal plant

**Other hazards**

No information available.

### 3. Composition/information on ingredients

**Pure substance/mixture****Mixture**

Chemical name	CAS No.	Weight-%	ENCS Number	ISHL No.
Ethylbenzene	100-41-4	29	(3)-28,(3)-60	(3)-28,(3)-60
2-Butoxyethanol	111-76-2	2.7	(2)-407,(2)-2424,(7)-97	(2)-407,(2)-2424,(7)-97
2,6-Di-tert-butyl-p-cresol	128-37-0	0.1-<1	(3)-540,(9)-1805	(3)-540,(9)-1805
Xylenes (o-, m-, p- isomers)	1330-20-7	16	(3)-3,(3)-60	(3)-3,(3)-60
Carbon black	1333-86-4	1-<10	-	(5)-5222,(5)-3328
1,1,2-Trichloroethane	79-00-5	0.1-<1	(2)-55	(2)-55
1-Methyl-2-pyrrolidone	872-50-4	0.1-<1	(5)-113	8-(1)-1014,8-(1)-1013
Chlorosulfone polyethylene, Inorganic filler	-	40-<50		

This product contains  $\geq 0.1$  -  $< 1.0\%$  of substance(s) that are classified for Skin sensitization Category 1/1B.

**Pollutant Release and Transfer Register (PRTR)**

The amount of the relevant substance in certain cases referenced in article 4(i)(a) or 4(i)(b) of the Enforcement Order of the Act on Confirmation, etc. of Release Amounts of Specific Chemical Substances in the Environment and Promotion of Improvements to the Management Thereof (PRTR Act) is calculated based on the conversion factors shown (with safety factor = 1 in cases where conversion factor information is not available)

Chemical name	Cabinet order name	Metal, CN, F, etc.	Conversion coefficient	Category	Ordinance number	Control number
Ethylbenzene	Ethylbenzene			Class I designated chemical substance	1-73	53
*	Ethylene Glycol Monobutyl			Class I designated	1-77	594

Chemical name	Cabinet order name	Metal, CN, F, etc.	Conversion coefficient	Category	Ordinance number	Control number
	Ether			chemical substance		
*	Xylene			Class I designated chemical substance	1-103	80

\* Refer to Cabinet order name

### Industrial Safety and Health Law

#### ISHL Notifiable Substances

Article 57-2 of the ISHL, Article 18-2, Item 1, Item 2, Table 9 and Item 3, Table 3 of Order for Enforcement

#### Harmful substances requiring risk assessment

Article 57-3 of the ISHL

Chemical name	Ministerial Ordinance Name	CAS No.	Implementation date
Ethylbenzene	Ethylbenzene	100-41-4	
2-Butoxyethanol	Ethylene glycol monobutyl ether	111-76-2	
2,6-Di-tert-butyl-p-cresol	2,6-Di-tert-butyl-p-cresol	128-37-0	
Xylenes (o-, m-, p- isomers)	Xylene	1330-20-7	
Carbon black	Carbon black	1333-86-4	
1,1,2-Trichloroethane	Trichloroethane	79-00-5	
1-Methyl-2-pyrrolidone	N-Methyl-2-pyrrolidone	872-50-4	

#### Harmful Substances Whose Names Are to be Indicated on the Label

Article 57 of ISHL, Article 18, Item 1, Item 2, Table 9 and Item 3, Table 3 of Order for Enforcement

Chemical name	Ministerial Ordinance Name	CAS No.	Implementation date
Ethylbenzene	Ethylbenzene	100-41-4	
2-Butoxyethanol	Ethylene glycol monobutyl ether	111-76-2	
Xylenes (o-, m-, p- isomers)	Xylene	1330-20-7	
Carbon black	Carbon black	1333-86-4	

#### Prevention of hazards due to specified chemical substances

Chemical name	CAS No.	Category	Ordinance number
Ethylbenzene	100-41-4	Group 2 specified chemical substance, special organic solvent, etc. (Ordinance on Prevention of Hazards Due to Specified Chemical Substances Art.2 Par.1, Item 2, 3-3)	2-03-3

#### Poisonous and Deleterious Substances Control Law

Not applicable

#### Act on the Evaluation of Chemical Substances and Regulation of Their Manufacture, etc. (CSCL)

The table below indicates ingredients above the cut-off threshold considered as relevant which are listed

Chemical name	CAS No.	Chemical Substances Control Law
Ethylbenzene	100-41-4	Priority assessment chemical substance
2-Butoxyethanol	111-76-2	Priority assessment chemical substance
2,6-Di-tert-butyl-p-cresol	128-37-0	Priority assessment chemical substance
Xylenes (o-, m-, p- isomers)	1330-20-7	Priority assessment chemical substance
1-Methyl-2-pyrrolidone	872-50-4	Priority assessment chemical substance

## 4. First-aid measures

#### General advice

Show this safety data sheet to the doctor in attendance. IF exposed or concerned: Get medical advice/attention. Immediate medical attention is required.

#### In case of inhalation

Remove to fresh air. Aspiration into lungs can produce severe lung damage. If breathing

	has stopped, give artificial respiration. Get medical attention immediately. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. If breathing is difficult, (trained personnel should) give oxygen. Get immediate medical advice/attention. Delayed pulmonary edema may occur. Immediate medical attention is required. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.
<b>In case of skin contact</b>	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If symptoms persist, call a physician.
<b>In case of eye contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area. If symptoms persist, call a physician. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
<b>In case of ingestion</b>	Do NOT induce vomiting. Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth to an unconscious person. ASPIRATION HAZARD IF SWALLOWED - CAN ENTER LUNGS AND CAUSE DAMAGE. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. Get immediate medical advice/attention.
<b>Most important symptoms/effects, acute and delayed</b>	Difficulty in breathing. Coughing and/ or wheezing. Dizziness. May cause redness and tearing of the eyes. Burning sensation. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.
<b>Self-protection of the first aider</b>	Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Do not breathe vapor or mist.
<b>Note to physicians</b>	Because of the danger of aspiration, emesis or gastric lavage should not be employed unless the risk is justified by the presence of additional toxic substances.

## 5. Fire-fighting measures

<b>Suitable Extinguishing Media</b>	Dry chemical. Carbon dioxide (CO <sub>2</sub> ). Water spray. Alcohol resistant foam.
<b>Unsuitable extinguishing media</b>	Do not scatter spilled material with high pressure water streams.
<b>Specific hazards arising from the chemical</b>	Risk of ignition. Keep product and empty container away from heat and sources of ignition. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. In the event of fire, cool container with water spray.
<b>Flammable properties</b>	HIGHLY FLAMMABLE: Will be easily ignited by heat, sparks or flames. Containers may explode when heated. Many liquids are lighter than water.
<b>Special Extinguishing Media</b>	Cool container with water spray.
<b>Special protective equipment and precautions for fire-fighters</b>	Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.
<b>Other information</b>	CAUTION: Use of water spray when fighting fire may be inefficient.

## 6. Accidental release measures

<b>Personal precautions, protective equipment and emergency procedures</b>	Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources
--	---

(no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Do not touch or walk through spilled material. Do not breathe vapor or mist. Avoid breathing vapors or mists.

<b>For emergency responders</b>	Use personal protection recommended in Section 8.
<b>Environmental precautions</b>	Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage if safe to do so. Prevent product from entering drains.
<b>Methods for containment</b>	Stop leak if you can do it without risk. Do not touch or walk through spilled material. A vapor suppressing foam may be used to reduce vapors. Dike far ahead of spill to collect runoff water. Keep out of drains, sewers, ditches and waterways. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal.
<b>Methods for cleaning up</b>	Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers.
<b>Prevention of secondary hazards</b>	Clean contaminated objects and areas thoroughly observing environmental regulations.
<b>Other information</b>	Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

## 7. Handling and storage

### Handling

<b>Advice on safe handling</b>	Take equipment measures listed in Section 8. Wear protection gear. Use personal protection equipment. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Remove contaminated clothing and shoes. Take off contaminated clothing and wash before reuse. Do not breathe vapor or mist. In case of insufficient ventilation, wear suitable respiratory equipment. Handle product only in closed system or provide appropriate exhaust ventilation.
--------------------------------	---

<b>Hygiene Measures</b>	Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Do not breathe vapor or mist. Remove and wash contaminated clothing and gloves, including the inside, before re-use.
-------------------------	---

### Storage

<b>Storage Conditions</b>	Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Keep out of the reach of children. Store locked up. Store away from other materials.
---------------------------	--

## 8. Exposure controls/personal protection

### Exposure guidelines

Chemical name	Japan Society of	ISHL Working	ACGIH TLV	Japan ISHA	Japan ISHA
---------------	------------------	--------------	-----------	------------	------------

	Occupational Health	Environmental Evaluation Standards - Administrative Control Levels		Workplace exposure limit - 8 hours	Workplace exposure limit - Short time
Ethylbenzene 100-41-4	TWA: 87 mg/m <sup>3</sup> TWA: 20 ppm S*	20 ppm	Ototoxicant - potential to cause hearing disorders TWA: 20 ppm	-	-
2-Butoxyethanol 111-76-2	Ceiling: 20 ppm Ceiling: 97 mg/m <sup>3</sup> S*	25 ppm	TWA: 20 ppm	-	-
2,6-Di-tert-butyl-p-cresol 128-37-0	-	-	TWA: 2 mg/m <sup>3</sup> inhalable fraction and vapor	10 mg/m <sup>3</sup>	-
Xylenes (o-, m-, p-isomers) 1330-20-7	TWA: 50 ppm TWA: 217 mg/m <sup>3</sup>	50 ppm	TWA: 20 ppm	-	-
Carbon black 1333-86-4	TWA: 4 mg/m <sup>3</sup> TWA: 1 mg/m <sup>3</sup>	-	TWA: 3 mg/m <sup>3</sup> inhalable particulate matter	-	-
1,1,2-Trichloroethane 79-00-5	TWA: 10 ppm TWA: 55 mg/m <sup>3</sup> S*	-	TWA: 10 ppm S*	-	-
1-Methyl-2-pyrrolidone 872-50-4	TWA: 1 ppm TWA: 4 mg/m <sup>3</sup> S*	-	-	-	-

**Biological monitoring indicator**

Chemical name	Japan Society of Occupational Health	ACGIH
Ethylbenzene 100-41-4	150 mg/g creatine - urine (Mandelic acid) - end of shift 15 µg/L - urine (Ethylbenzene) - end of shift 200 mg/g creatine - urine (Mandelic acid and Phenylglyoxylic acid) - end of shift at end of work week	0.15 g/g creatinine - urine (Sum of mandelic acid and phenylglyoxylic acid) - end of shift
2-Butoxyethanol 111-76-2	200 mg/g creatine - urine (total Butoxyacetic acid) - end of shift	200 mg/g creatinine - urine (Butoxyacetic acid with hydrolysis) - end of shift
Xylenes (o-, m-, p-isomers) 1330-20-7	800 mg/L - urine (total (o-, m-, p-) Methylhippuric acid) - end of shift at end of work week	1.5 g/g creatinine - urine (Methylhippuric acids) - end of shift
1-Methyl-2-pyrrolidone 872-50-4	-	100 mg/L - urine (5-Hydroxy-N-methyl-2-pyrrolidone) - end of shift

**Engineering controls**

Showers  
Eyewash stations  
Ventilation systems.

**Environmental exposure controls**

Install local ventilation or seal source of substances. Install safety shower, hand wash, and eye wash station. Clearly indicate the location.

**Personal protective equipment****Respiratory protection**

In case of inadequate ventilation wear respiratory protection. If workers are exposed to gases or vapors, consider wearing respiratory protective equipment (e.g., gas masks). When handling highly concentrated chemicals, consider wearing an air-supplied respirator.

When selecting a respirator, the following points should be considered.

- Do not use masks in areas where the oxygen concentration is less than 18%.
- When using a gas mask in an environment where workers are exposed to dust, use an absorbent can with dustproof function.
- Select a gas mask with performance and construction suitable for the work in accordance with the Japanese Industrial Standard (JIS T8152), and refer to the data provided in the instruction manual.

<b>Hand protection</b>	Wear suitable gloves. Impervious gloves. Consider wearing impervious protective gloves. When selecting protective gloves, the following points should be considered. -Referring to the impermeability class, etc. listed in the instruction manual, set a use time that allows for the work, and use protective gloves within that time range.
<b>Eye/face protection</b>	Tight sealing safety goggles.
<b>Skin and body protection</b>	Wear suitable protective clothing. Long sleeved clothing. Chemical resistant apron. Antistatic boots.

## 9. Physical and chemical properties

### Information on basic physical and chemical properties

Physical state	Liquid
Color	Black
Odor	Solvent odor
<u>Property</u>	<u>Values</u>
Melting point / freezing point	no data available
Initial boiling point and boiling range	
Flammability	no data available
Upper/lower flammability or explosive limits	
Upper flammability or explosive limits	no data available
Lower flammability or explosive limits	no data available
Flash point	28 °C
Evaporation rate	no data available
Autoignition temperature	no data available
Decomposition temperature	no data available
pH	no data available
Viscosity	
Kinematic viscosity	no data available
Dynamic viscosity	8.5 Pa·s
Water solubility	Slightly soluble
Solubility(ies)	no data available
Partition Coefficient (n-octanol/water)	no data available
Vapor pressure	no data available
Density and/or relative density	
Relative density	1.2
Liquid Density	no data available
Bulk density	no data available
Relative vapor density	no data available
Particle characteristics	
Particle Size	no data available
Particle Size Distribution	no data available

### Other information

Explosive properties no data available  
 Oxidizing properties No data available

## 10. Stability and reactivity

**Chemical stability** Stable under normal conditions

**Possibility of hazardous reactions** No hazardous reaction could occur under normal condition.

**Conditions to avoid** Heat, flames and sparks. Excessive heat.

**Incompatible materials** Strong oxidizing agents. Strong acids. Strong bases.

**Hazardous decomposition products** May generate harmful gas by incineration.

## 11. Toxicological information

### Acute toxicity

#### Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 1,915.60 mg/kg  
 ATEmix (dermal) 1,920.60 mg/kg  
 ATEmix (inhalation-vapor) 7.55 mg/l  
 ATEmix (inhalation-dust/mist) 1.58 mg/l

#### Unknown acute toxicity

24.33501 % of the mixture consists of ingredient(s) of unknown acute oral toxicity  
 44.70701 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity  
 30.89301 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)  
 35.96301 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist)

#### Numerical measures of toxicity - Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Ethylbenzene	= 3500 mg/kg ( Rat )	= 15400 mg/kg ( Rabbit )	= 17.4 mg/L ( Rat ) 4 h
2-Butoxyethanol	= 470 mg/kg ( Rat )	= 435 mg/kg ( Rabbit )	= 450 ppm ( Rat ) 4 h = 486 ppm ( Rat ) 4 h
2,6-Di-tert-butyl-p-cresol	> 2930 mg/kg ( Rat )	> 2000 mg/kg ( Rat )	-
Xylenes (o-, m-, p- isomers)	= 3500 mg/kg ( Rat )	> 4350 mg/kg ( Rabbit )	= 29.08 mg/L ( Rat ) 4 h
Carbon black	> 15400 mg/kg ( Rat )	-	> 4.6 mg/m <sup>3</sup> ( Rat ) 4 h
1,1,2-Trichloroethane	= 836 mg/kg ( Rat )	= 5371 mg/kg ( Rabbit )	= 2.78 mg/L ( Rat ) 8 h
1-Methyl-2-pyrrolidone	= 3914 mg/kg ( Rat )	= 8 g/kg ( Rabbit )	> 5.1 mg/L ( Rat ) 4 h

#### Abbreviations and acronyms

Rat: Rat

Rabbit: Rabbit

#### Symptoms

Difficulty in breathing. Coughing and/ or wheezing. Dizziness. Redness. May cause redness and tearing of the eyes. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

#### Product Information

<b>Ingestion</b>	Specific test data for the substance or mixture is not available. Potential for aspiration if swallowed. May cause lung damage if swallowed. Aspiration may cause pulmonary edema and pneumonitis. May be fatal if swallowed and enters airways. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. (based on components).
<b>Inhalation</b>	Specific test data for the substance or mixture is not available. Aspiration into lungs can produce severe lung damage. May cause pulmonary edema. Pulmonary edema can be fatal. May cause irritation of respiratory tract. Toxic by inhalation. (based on components). May cause drowsiness or dizziness. Harmful by inhalation.
<b>Skin contact</b>	Repeated exposure may cause skin dryness or cracking. Specific test data for the substance or mixture is not available. Causes skin irritation. (based on components).
<b>Eye contact</b>	Specific test data for the substance or mixture is not available. May cause irritation. Causes serious eye irritation. (based on components). May cause redness, itching, and pain.
<b>Skin corrosion/irritation</b>	Classification based on data available for ingredients. Causes skin irritation.
<b>Serious eye damage/eye irritation</b>	Classification based on data available for ingredients. Causes serious eye irritation.
<b>Germ cell mutagenicity</b>	Contains a known or suspected mutagen. Classification based on data available for ingredients. May cause genetic defects.
<b>Carcinogenicity</b>	The hazardous substance(s) which is (are) any of the following substances and listed on section 3 is (are) embedded in the product and not available as respirable dusts. When used as intended or as supplied, the product will not pose hazards of the hazardous substance(s). Silica, Quartz, Carbon black, Titanium oxide, Crystalline silica. Contains a known or suspected carcinogen. Classification based on data available for ingredients. Suspected of causing cancer.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	Japan	IARC
Ethylbenzene 100-41-4	2	Group 2B
2-Butoxyethanol 111-76-2	-	Group 3
2,6-Di-tert-butyl-p-cresol 128-37-0	-	Group 3
Xylenes (o-, m-, p- isomers) 1330-20-7	-	Group 3
Carbon black 1333-86-4	2	Group 2B
1,1,2-Trichloroethane 79-00-5	2	Group 3

#### Legend

**IARC (International Agency for Research on Cancer)**

Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not Classifiable as to Carcinogenicity in Humans

<b>Reproductive toxicity</b>	Classification based on data available for ingredients. May damage fertility or the unborn child. May cause harm to breast-fed children.
------------------------------	--

**STOT - single exposure**

Based on the classification criteria of the Globally Harmonized System as adopted in the country or region with which this safety data sheet complies, this product has been determined to cause systemic target organ toxicity from acute exposure. (STOT SE). Causes damage to organs if swallowed. Causes damage to organs in contact with skin. May cause respiratory irritation. May cause drowsiness or dizziness.

Causes damage to the following organs: Central nervous system, kidneys, liver, Respiratory system.

May cause damage to the following organs: blood system.

**STOT - repeated exposure**

The hazardous substance(s) which is (are) any of the following substances and listed on section 3 is (are) embedded in the product and not available as respirable dusts. When used as intended or as supplied, the product will not pose hazards of the hazardous substance(s). Silica, Quartz, Carbon black, Crystalline silica. Causes damage to organs through prolonged or repeated exposure.

Causes damage to the following organs through prolonged or repeated exposure: nervous system, Respiratory system.

May cause damage to the following organs through prolonged or repeated exposure: auditory organs, blood system.

**Aspiration hazard**

May be fatal if swallowed and enters airways.

## 12. Ecological information

**Ecotoxicity**

Toxic to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Crustacea
Ethylbenzene	EC50: =4.6mg/L (72h, Pseudokirchneriella subcapitata) EC50: >438mg/L (96h, Pseudokirchneriella subcapitata) EC50: 2.6 - 11.3mg/L (72h, Pseudokirchneriella subcapitata) EC50: 1.7 - 7.6mg/L (96h, Pseudokirchneriella subcapitata)	LC50: 11.0 - 18.0mg/L (96h, Oncorhynchus mykiss) LC50: =4.2mg/L (96h, Oncorhynchus mykiss) LC50: 7.55 - 11mg/L (96h, Pimephales promelas) LC50: =32mg/L (96h, Lepomis macrochirus) LC50: 9.1 - 15.6mg/L (96h, Pimephales promelas) LC50: =9.6mg/L (96h, Poecilia reticulata)	EC50: 1.8 - 2.4mg/L (48h, Daphnia magna)
2-Butoxyethanol	-	LC50: =1490mg/L (96h, Lepomis macrochirus) LC50: =2950mg/L (96h, Lepomis macrochirus)	EC50: >1000mg/L (48h, Daphnia magna)
2,6-Di-tert-butyl-p-cresol	EC50: =6mg/L (72h, Pseudokirchneriella subcapitata) EC50: >0.42mg/L (72h, Desmodesmus subspicatus)	-	-
Xylenes (o-, m-, p- isomers)	-	LC50: =13.4mg/L (96h, Pimephales promelas) LC50: 2.661 - 4.093mg/L (96h, Oncorhynchus mykiss) LC50: 13.5 - 17.3mg/L (96h, Oncorhynchus mykiss) LC50: 13.1 - 16.5mg/L (96h,	EC50: =3.82mg/L (48h, water flea) LC50: =0.6mg/L (48h, Gammarus lacustris)

		Lepomis macrochirus) LC50: =19mg/L (96h, Lepomis macrochirus) LC50: 7.711 - 9.591mg/L (96h, Lepomis macrochirus) LC50: 23.53 - 29.97mg/L (96h, Pimephales promelas) LC50: =780mg/L (96h, Cyprinus carpio) LC50: >780mg/L (96h, Cyprinus carpio) LC50: 30.26 - 40.75mg/L (96h, Poecilia reticulata)	
1,1,2-Trichloroethane	EC50: =167mg/L (96h, Desmodesmus subspicatus)	LC50: =81.6mg/L (96h, Pimephales promelas) LC50: 35 - 47mg/L (96h, Lepomis macrochirus)	EC50: =18mg/L (48h, Daphnia magna) EC50: 57 - 110mg/L (48h, Daphnia magna)
1-Methyl-2-pyrrolidone	EC50: >500mg/L (72h, Desmodesmus subspicatus)	LC50: =832mg/L (96h, Lepomis macrochirus) LC50: =1072mg/L (96h, Pimephales promelas) LC50: =1400mg/L (96h, Poecilia reticulata)	EC50: =4897mg/L (48h, Daphnia magna)

**Percentage for unknown hazards** 0 % of the mixture consists of component(s) of unknown hazards to the aquatic environment.

**Persistence and degradability** No information available.

#### Bioaccumulation

#### Component Information

Chemical name	Partition coefficient
Ethylbenzene 100-41-4	3.6
2-Butoxyethanol 111-76-2	0.81
2,6-Di-tert-butyl-p-cresol 128-37-0	5.1
Xylenes (o-, m-, p- isomers) 1330-20-7	3.15
1,1,2-Trichloroethane 79-00-5	1.89
1-Methyl-2-pyrrolidone 872-50-4	-0.46

**Mobility in soil** No information available.

**Hazardous to the ozone layer** Classification not possible. Based on available data, the classification criteria are not met.

**Other adverse effects** No information available.

### 13. Disposal considerations

**Waste from residues/unused products** Dispose of in accordance with national, state and local regulations. Consult industrial waste management companies for waste. Do not release this product to natural environment nor reclaim.

Contaminated packaging

Dispose containers as same as residual of this product.

## 14. Transport information

### IMDG

UN number or ID number	UN1992
UN proper shipping name	Flammable liquid, toxic, n.o.s.
Description	UN1992, Flammable liquid, toxic, n.o.s. (Ethanol, Isopropyl alcohol), 3 (6.1), III, (28°C c.c.)
Transport hazard class(es)	3
Subsidiary hazard class	6.1
Packing group	III
Marine pollutant	P
EmS-No.	F-E, S-D
Special Provisions	223, 274

### ADR

UN number or ID number	1992
UN proper shipping name	Flammable liquid, toxic, n.o.s.
Description	1992, Flammable liquid, toxic, n.o.s. (Cyfluthrin [3-(2,2-dichloroethenyl)-2,2-dimethylcyclopropanecarboxylic acid, cyano(4-fluoro-3-phenoxyphenyl)methylester], Triclosan), 3 (6.1), III, (D/E)
Transport hazard class(es)	3
Subsidiary hazard class	6.1
Packing group	III
Environmental hazards	Yes
ERG Code	3P
Special Provisions	274

### IATA

UN number or ID number	UN1992
UN proper shipping name	Flammable liquid, toxic, n.o.s.
Description	UN1992, Flammable liquid, toxic, n.o.s. ((S)-Butan-2-ol, Cyanofenphos (ISO)), 3 (6.1), III
Transport hazard class(es)	3
Subsidiary hazard class	6.1
Packing group	III
Special Provisions	A3

### Japan

UN number or ID number	UN1992
UN proper shipping name	Flammable liquid, toxic, n.o.s.
Description	UN1992, Flammable liquid, toxic, n.o.s. (), 3 (6.1), III
Transport hazard class(es)	3
Subsidiary hazard class	6.1
Packing group	III
Special Provisions	223, 274

## 15. Regulatory information

### National regulations

#### Pollutant Release and Transfer Register (PRTR)

Applies See section 3 for more information

#### Industrial Safety and Health Law

#### Prevention of hazards due to specified chemical substances

Specified chemical substances (Group 2) - Industrial Safety and Health Law enforcement order Table 3 (related to article 6, article 9-3, article 21, article 22 and the Ordinance on Prevention of Hazards Due to Specified Chemical Substances)

#### Harmful Substances Requiring Workers to Subject to Medical Exams

Medical Examination - Industrial Safety and Health Law article 66, enforcement order article 22, and the Ordinance on Prevention of Hazards Due to Specified Chemical Substances, Table 5

#### **Ordinance on Prevention of Organic Solvent Poisoning**

Organic solvents class 2 - Industrial Safety and Health Law enforcement order Table 6-2 (related to article 6, article 21, article 22, and the Ordinance on Prevention of Organic Solvent Poisoning)

#### **Substances under special supervision**

Specified chemical substance subject to article 38-3 and 38-4 of the Ordinance on Prevention of Hazards Due to Specified Chemical Substances

#### **ISHL Notifiable Substances**

Article 57-2 of the ISHL, Article 18-2, Item 1, Item 2, Table 9 and Item 3, Table 3 of Order for Enforcement

#### **Harmful substances requiring risk assessment**

Article 57-3 of the ISHL

#### **Harmful Substances Whose Names Are to be Indicated on the Label**

Article 57 of ISHL, Article 18, Item 1, Item 2, Table 9 and Item 3, Table 3 of Order for Enforcement

#### **Guidelines for Carcinogenic substances**

Chemical substances specified by the Minister of Health, Labor and Welfare based on the provisions of Article 28, Paragraph 3 of the Industrial Safety and Health Act

#### **Poisonous and Deleterious Substances Control Law**

Not applicable

#### **Explosives Control Law**

No

#### **High Pressure Gas Safety Act**

Not applicable

#### **Fire Service Law:**

Flammable liquids, group 4, 2nd class petroleums, water-insoluble, hazard rank III, 1000 liters

#### **Act on the Evaluation of Chemical Substances and Regulation of Their Manufacture, etc. (CSCL)**

The table below indicates ingredients above the cut-off threshold considered as relevant which are listed

Chemical name	CAS No.	Chemical Substances Control Law
Ethylbenzene	100-41-4	Priority assessment chemical substance
2-Butoxyethanol	111-76-2	Priority assessment chemical substance
2,6-Di-tert-butyl-p-cresol	128-37-0	Priority assessment chemical substance
Xylenes (o-, m-, p- isomers)	1330-20-7	Priority assessment chemical substance
1-Methyl-2-pyrrolidone	872-50-4	Priority assessment chemical substance

#### **Ship (Marine Transportation) Safety Act**

See section 14 for more information

#### **Civil Aeronautics Act**

See section 14 for more information

#### **Act on Port Regulation Law**

See section 14 for more information

## **16. Other information**

**Issuing Date** 14-Oct-2021

**Revision date** 30-Oct-2023

#### **Key or legend to abbreviations and acronyms used in the safety data sheet**

Legend Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA	TWA (time-weighted average)	Ceiling	Maximum limit value
*	Skin designation	+	Sensitizers

#### **Key literature references and sources for data used to compile the SDS**

JIS Z 7252:2019 Classification of chemicals based on "Globally Harmonized System of Classification and Labelling of Chemicals (GHS)"

JIS Z 7253:2019 Hazard communication of chemicals based on GHS-Labeling and Safety Data Sheet (SDS)

#### **Disclaimer**

This SDS complies with the requirements of JIS Z 7252:2019 and JIS Z 7253:2019 (Japan). The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.