D&LLTechnologies





Dell UltraSharp 27 Thunderbolt[™] Hub Monitor | **u2724DE**

The world's #1 monitor company*

* Dell monitors are #1 Worldwide for 9 years! Source: IDC Worldwide Quarterly PC Monitor Tracker, Q2 2023. From 2014 to 2023.

Bring your visual comfort to the next level



TÜVRIndenland CERTIFIED

Experience a new level of visual comfort and productivity with this hub monitor certified by TÜV Rheinland for 5-star eye comfort.¹ Designed with extensive connectivity and the power of Thunderbolt 4.

Enhanced visual comfort

Protect your eyes from harmful blue light emission without sacrificing color with improved ComfortView Plus that reduces harmful blue light to less than 35%. Combined with 120Hz refresh rate and ambient light sensing, it achieves 5 star certification from TÜV Rheinland for all-day eye comfort. Experience deeper blacks with 2000:1 contrast ratio on an IPS Black panel. See vibrant colors with 98% DCI-P3, 98% Display P3, 100% sRGB and 100% BT.709 color space and easily calibrate your colors with Dell Color Management software.

Easier connections

Streamline productivity with a single Thunderbolt 4 cable that transmits data and video signals while delivering up to 90W of power and 2.5GbE speeds with RJ45 connectivity for a fast and stable network connection. Expand your productivity by connecting 2 PCs and multitask seamlessly across both PC with KVM, Picture-in-Picture (PiP) and Picture-by-Picture (PbP).

Premium design

Designed with a premium finish, this monitor with a built-in cable management system reduces cable clutter. It is adjustable to fit the way you work and be comfortable all day. Built with sustainable practices for the performance you need while meeting EPEAT® Gold, ENERGY STAR® and TCO Certified Edge Displays criteria.

Exceptional contrast

See incredible color and superior black performance with a contrast ratio of 2,000:1 with IPS Black panel technology.

Get a clearer view QHD (2560 x 1440) resolution on a 27" monitor.



Extensive connectivity Stay connected to multiple devices with Thunderbolt 4 (up to 90W power delivery), USB-A, DP1.4 and HDMI ports.

Adjust to your comfort Tilt, swivel, pivot and height adjustment (150mm max). Connect two PC sources and multitask efficiently with **Picture-by-Picture** / **Picture-in-Picture** and **KVM** (with **Auto KVM**).

ENERGY STAR[®], TCO Certified Edge, EPEAT[®] Gold registered. Improved **ComfortView Plus** reduces harmful blue light emissions to less than 35% without sacrificing color performance.

True brilliance

Enjoy 1.07 billion colors and a wide color coverage across industry standards, including 98% DCI-P3, 98% Display P3, 100% sRGB and 100% BT.709.

Easily connect your accessories and devices with USB-A and USB-C quick access ports.

Ambient Light Sensor Built-in Ambient Light

optimizes brightness and color temperature based

Sensor intelligently

on your surroundings.

Fast and

stable Ethernet

Get up to 2.5 GbE with

RJ45 port that comes

Wake on Lan features.

with PXE boot, Mac Address pass-thru¹ and

1 MAC Address pass-through functionality is tested to work with most Dell PC systems. Functionality on non-Dell systems may vary.

D&LLTechnologies

Exceptional contrast and stunning colors



Exceptional contrast

See incredible color and deeper blacks with a contrast ratio of 2,000:1 with IPS Black panel technology. With a wide 178°/178° viewing angle, images remain spectacular, from virtually any angle.

True brilliance

With 1.07 billion colors and a wide color gamut (98% DCI-P3, 98% Display P3, 100% sRGB and 100% BT.709) every color will stand out.

Dell Color Management

Easily calibrate your monitor's colors with the new Dell Color Management software¹, developed in partnership with Calman certification. Create and store preset color profiles you can save and use later on your monitor.

1 Compatible with external colorimeter (listed below), sold separately. Portrait Displays: C6 HDR2000, X-Rite: I1Display Pro, I1Display Pro Plus, Klein Instruments: K10, Calibrate: ColorChecker Display Pro, ColorChecker Display Plus.

Connectivity that drives productivity

Thunderbolt Hub monitors offer extensive connectivity options including Thunderbolt 4 (up to 90W power delivery), RJ45 for wired Ethernet access, super speed USB for fast data transfers, and more.



- 1 Dell adheres to standard USB-C specifications and protocol. Functionality with non-Dell USB-C systems may vary.
- 2 Via quick access USB-C port.
- 3 The power sync feature on this Dell USB-C Monitor enables start up and wake-on-demand on compatible Dell PCs. Please check your Dell PC to ensure support of this featur
- 4 MAC Address pass-through functionality is tested to work with most Dell PC systems. Functionality on non-Dell systems may vary.

DCLTechnologies





Environmental standards

This monitor is made from 85% PCR (Post-consumer Recyclable) plastic in the design¹, 90% recycled aluminum and meets the latest environmental standards such as ENERGY STAR[®], and TCO Certified Edge, and are EPEAT[®] Gold² registered.

Eco-conscious packaging

Dell monitors ship in boxes made with 100% renewable content that is also 100% recyclable.³

Energy conservation

Save energy with PowerNap⁴, a feature that dims or puts your monitor to sleep when it's not in use.

By weight of the total weight of plastic parts in product. Excludes printed circuit boards, labels, cables, connectors,

- 2 EPEAT registered where applicable. EPEAT registration varies by country. See www.epeat.net for registration status by country.
 3 Applies to all Dell monitors launched since 2023 Made from ESC mix sources which is a mix of material from ESC certified forests, recycled content and/or ESC controlled wood. Based on internal analysis. August 2023
- 4 Enabled by Dell Display Manager.

Designed for you

Crafted with a premium platinum silver finish, this stylish Dell UltraSharp 27 Thunderbolt Hub monitor fits both home and office environments.





Work comfortably

Experience made-for-you comfort by tilting, swiveling, pivoting and adjusting the height of your monitor (150mm max).

Dell Display Manager



Modern Intuitive User Interface

New modern user interface for ease of use and personalization of features with Menu launcher.

Productive at every level

Easy Arrange allows you to easily tile multiple applications across one or more screens with 48 pre-set window partitions and the ability to personalize up to five windows, giving you improved multitasking abilities. Easy Arrange Memory save the placement of your programs and applications in the layouts and restore them when you select the preferred layout.

Stay updated

Get automatic notification anytime for new updates on monitor firmware¹ and software.

Optimize front of screen experience

Get uniform color experience from your monitor seamlessly by matching the color preset of the monitor¹ and the supported ICC profile.

Easy setup and sharing of accessories

Setup a single keyboard and mouse to be shared easily between multiple PCs with USB KVM wizard.¹ Quick access menu or hotkey allow convenient fast switching between PCs.

Easy deployment

DDM is compatible with management tools such as SCCM, InTune and Command Line Interface scripts for easy IT integration and deployment with asset management.

Download Dell Display Manager

Ports & Slots



- 1 Security lock slot¹
- 2 Power connector
- HDMI (HDCP 1.4)(Supports up to QHD 2560 x 1440 120Hz TMDS, VRR as per specified in HDMI2.1)
- 4 DisplayPort 1.4
- 5 Stand lock
- **6** DisplayPort 1.4 (out)
- 7 Thunderbolt[™] 4 downstream port (15W) for daisy-chaining
- 8 Thunderbolt[™] 4 upstream port (Video + Data). Alternate mode with DisplayPort 1.4, power delivery up to 90W.

- 9 USB Type-C upstream port (SuperSpeed USB 10Gbps, USB 3.2 Gen 2)
- **10** 2 x USB Type-A downstream port (SuperSpeed USB 10Gbps, USB 3.2 Gen 2)
- **11** Audio line out
- 12 USB Type-A downstream port (SuperSpeed USB 10Gbps, USB 3.2 Gen 2)
- 13 RJ45 port
- 14 USB Type-A downstream port (SuperSpeed USB 10Gbps, USB 3.2 Gen 2) with BC1.2 power charging
- **15** USB Type-C downstream port (SuperSpeed USB 10Gbps, USB 3.2 Gen 2) with power charging (15W)

1 Based on Kensington Security Slot*

TECHNICAL SPECIFICATION

596.74 mm x 335.66 mm (23.49" x 13.22")

684.70 mm (27.00 inches)

IPS Black Technology

2560 x 1440 at 120 Hz

Anti-Glare with 3H hardness

178° vertical / 178° horizontal

0.2331 mm x 0.2331 mm

2000 to 1 (typical)

350 cd/m² (typical)

8 ms (Normal) 5 ms (Fast)

5 Stars

Yes

Yes

Yes

No

1 x Audio line-out¹

108 97

16:9

LED

Dell UltraSharp 27 Thunderbolt™ Hub Monitor - U2724DE

FEATURE	
MODEL	
DIAGONAL VIEWING SIZE	

PRESET DISPLAY AREA $(H \times V)$ PANEL TYPE

> DISPLAY SCREEN COATING

MAXIMUM PRESET RESOLUTION

VIEWING ANGLE

PIXEL PITCH

PIXEL PER INCH (PPI)

CONTRAST RATIO

ASPECT RATIO

BACKLIGHT TECHNOLOGY

BRIGHTNESS

RESPONSE TIME

AMBIENT LIGHT SENSOR

TÜV FYF COMFORT CERTIFICATION CONNECTIVI

ADJUSTABILI

KEYBOARD, VIDEO AND MOUSE (KVM)

PRP / PIP

DAISY CHAIN

AVAILABILITY

AUDIO OUTPUT

DELL DISPLAY

MANAGER

BUILT-IN SPEAKER

ТҮ	 1 x DP 1.4 (DRR for Microsoft Windows) (Supports 2 x QHD 120Hz 8 bit) 1 x DP out
	 1 x HDMI (HDCP 1.4)(Supports up to QHD 2560 x 1440 120Hz TMDS, VRR as per specified in HDMI 2.1)
	 1 x Thunderbolt[™] 4 downstream (15W) only suitable for video output under Daisy Chain
	 1 x Thunderbolt[™] 4 upstream (Thunderbolt mode and alternate mode with DisplayPort 1.4, USB 3.2 Gen 2 upstream port, Power Delivery (PD) up to 90 W)

• 1 x USB-C	upstream (Data only, USB 3.2 Gen 2, 10Gbps)
• 3 x USB-A	(USB 3.2 Gen 2 10Gbps)
 1 x audio li 	neout
• 1 x RJ45 (2	2.5GbE)

Yes, auto brightness and color temperature adjustmemt

	Quick Access: • 1 x USB-A (USB 3.2 Gen 2 10Gbps) with BC 1.2 • 1 x USB-C (USB 3.2 Gen 2 10Gbps, 15W)
ТҮ	Height adjustable (150 mm) Tilt (-5° to 21°) Swivel (-45° to 45°) Pivot (-90° to 90°)

Yes, Easy Arrange, Other key features

SPECIFICATIONS - SERVICE / SUPPORT DETAILS	3-Year Advanced Exchange Service and Premium Panel Exchange
COLOR GAMUT	 100% sRGB 100% BT.709 98% Display P3 98% DCI-P3 1.07 billion colors Delta E < 2 (average) (sRGB, BT.709, Display P3, DCI-P3)
HEIGHT WITH STAND (COMPRESSED ~ EXTENDED)	385.58 mm ~ 535.58 mm (15.18" ~ 21.09")
WIDTH WITH STAND	612.24 mm (24.10")
DEPTH WITH STAND	192.28 mm (7.57")
HEIGHT WITHOUT STAND	352.51 mm (13.88")
WIDTH WITHOUT STAND	612.24 mm (24.10")
DEPTH WITHOUT STAND	50.12 mm (1.97")
WEIGHT (PANEL ONLY - FOR VESA MOUNT)	5.23 kg (11.53 lb)
WEIGHT (WITH STAND ASSEMBLY AND CABLES)	7.37 kg (16.25 lb)
WEIGHT (WITH PACKAGING)	10.21 kg (22.51 lb)
SECURITY	Security lock slot (cable lock sold separately) Anti-theft stand lock slot (to lock stand to monitor using screw)
COMPLIANT STANDARDS	ENERGY STAR® certified monitor EPEAT® registered where applicable. EPEAT registration varies by country. See www.eneat.net.for.registration

ν

FEATURE

STANDARDS

VESA mounting holes (100 mm x 100 mm - b VESA Cover)
Operating: 0°C to 40°C (32°F to 104°F) Non-operating: -20°C to 60°C (-4°F to 140°F)
Operating: 10% to 80% (non-condensing) Non-Operating: 5% to 90% (non-condensing)
Operating: 5000 m (16404 ft) max Non-Operating: 12192 (40000 ft) max
100 VAC to 240 VAC / 50 Hz or 60 Hz \pm 3 Hz (typical)
0.3 W (Off mode) ² 0.5 W (Standby mode) ² 1.5 W (Networked standby mode) ² 24.4 W (On mode) ²

ENERGY EFFICIENCY CLASS (A TO G SCALE)

HUMIDITY RANGE

VOLTAGE REQUIRED

POWERCONSUMPTION

NORMAL OPERATION

ALTITUDE

WHAT'S INCLUDED

Monitor. Stand Riser. Stand Base 1 x Power cable 1 x DP Cable (DP to DP) - 1.8 m 1 x USB-A to USB-C Gen 2 cable - 1 m 1 x Thunderbolt™ 4 cable - 1 m Quick setup guide Safety, Environmental and Regulatory Information Factory calibration report

Headphone usage is not supported for the audio line out connector

As defined in EU 2019/2021 and EU 2019/2013.

3 Max brightness and contrast setting with maximum power loading on all USB ports.

4 Pon: Power consumption of On Mode as defined in Energy Star 8.0. TEC: Total energy consumption in kWh as defined in Energy Star 8.0 version. **TECHNICAL SPECIFICATION**

RoHS Compliant
BFR/PVC Free monitor (excluding external cables).
Arsenic-Free glass and Mercury-Free for the panel only FLAT PANEL MOUNT INTERFACE **TEMPERATURE RANGE**

0 Hz ± 3 Hz / 2.65 A

varies by country. See www.epeat.net for registration status by country. • TCO Certified & TCO Certified Edge

100 mm - behind attached

225 W (Max.)³ 18.9 W (Pon)⁴ 65 kWh (TEĆ)4 F Ť

Steadfast reliability

As the No. 1 monitor company worldwide*, we take pride in our unyielding commitment to quality and the utmost in customer satisfaction.

Premium Panel Exchange

Dell Premium Panel Exchange¹ allows a free monitor replacement during the Limited Hardware Warranty² period even if only one bright pixel is found.

Advanced Exchange Service

This monitor comes with a 3-year Advanced Exchange Service³ so that if a replacement becomes necessary, it will be shipped to you the next business day during your 3-year Limited Hardware Warranty.²

ProSupport

Upgrade to 24x7 specialized technical phone support with the Dell ProSupport option.⁴

* Dell monitors are #1 Worldwide for 9 years! Source: IDC Worldwide Quarterly PC Monitor Tracker, Q2 2023. From 2014 to 2023.

- 1 Applicable to Dell UltraSharp, P Series, and C Series desktop monitors.
- 2 For copy of Ltd Hardware Warranty, write to Dell USA LP, Attn: Warranties, One Dell Way, Round Rock, TX 78682 or see https://www.dell.com/warranty.
- 3 Advanced Exchange: Dell will send you a replacement monitor the next business day in most cases, if deemed necessary after phone/online diagnosis. Shipping times may vary by location and for monitors 55° and above. Fee charged for failure to return defective unit. See dell.com/servicecontracts/global.
- 4 Availability varies, please visit www.dell.com/support for details. In some countries, hours for in-region support may vary. Support after local business hours may be provided in a language other than the local language.

Technical specifications subject to change without prior notice. Product availability varies by country. Please contact your Dell representative for more information.

© 2023 Dell Inc. or its subsidiaries. All Rights Reserved. Dell Technologies, Dell, EMC, Dell EMC and other trademarks are trademarks of Dell Inc. or its subsidiaries. Other trademarks may be trademarks of their respective owners. USB Type-C[®] and USB-C[®] are registered trademarks of USB Implementers Forum. Thunderbolt and the Thunderbolt logo are trademarks of Intel Corporation in the U.S. and/or other countries.