



Cordless Pruning Saw

DUC150 150 mm (6")
DUC101 / UC100D 100 mm (4")

Satisfy Professional's Needs



photo: DUC150

photo: DUC101

photo: UC100D

DUC150



Net weight*
**1.7 -
2.0 kg**



DUC101



Net weight*
**1.6 -
2.0 kg**



UC100D



Net weight*
**1.5 -
1.6 kg**





photo: DUC150



photo: DUC150



photo: DUC101

Lightweight yo

Movable guard

covers the upper side of guide bar, and opens gradually wider as saw chain cuts deeper in branch.



Guide bar length

DUC150: **150mm**

DUC101 / UC100D: 100mm

Work amount

Test conditions:
Cut ø50 cedar rod under an optimal pressing load of 20N or less
on cutting edge.
Saw chain: 80TXL

DUC150 / DUC101

210 pcs.

Battery: BL1830B

UC100D

73 pcs.

Battery: BL1021B

BL
MOTOR

Compact and
lightweight
BL motor



XPT

eXtreme Protection Technology

et easy-to-use



photo: DUC150

Automatic chain lubrication



minimizes the chance that saw chain will stall due to forgetting to supply chain oil.

New Tool-less change and tension adjustment of saw chain



- Simply loosen and re-tighten the lever to automatically adjust the tension of saw chain.
- This easy-to-operate large lever is designed to be pulled and turned easily.



photo: DUC101



photo: UC100D

Accessories

File holder set

4.0 mm (5/32")



Guide bar



Chain oil

100mL
(country-specific)



Saw chain



Holster set

Storage and carrying of the machine
For both 100mm/150mm models



Charging Time

						
	DC10SB	DC10WD		DC18RC	DC18SD	
BL1016 1.5Ah	22 min	50 min		BL1815N 1.5Ah	15 min	30 min
				BL1820B 2.0Ah	24 min	45 min
BL1021B 2.0Ah	30 min	70 min		BL1830B 3.0Ah	22 min	60 min
				BL1840B 4.0Ah	36 min	90 min
BL1041B 4.0Ah	60 min	130 min		BL1850B 5.0Ah	45 min	110 min
				BL1860B 6.0Ah	55 min	130 min

Cordless Pruning Saw

DUC150 150 mm (6")

	DUC150	DUC101	UC100D
 Brake			
 Automatic Oiling			
Saw chain	Type: 80TXL / Gauge: 1.1 mm (0.043") Pitch: 0.325" / Number of links: 32	Type: 80TXL / Gauge: 1.1 mm (0.043") Pitch: 0.325" / Number of links: 26	Type: 80TXL / Gauge: 1.1 mm (0.043") Pitch: 0.325" / Number of links: 26
Guide bar length	150 mm (6")	100 mm (4")	100 mm (4")
Max cutting length	161 mm	111 mm	111 mm
Chain speed	8.0 m/s (480 m/min) (1,570 FPM)	8.0 m/s (480 m/min) (1,570 FPM)	8.0 m/s (480 m/min) (1,570 FPM)
Chain oil tank volume	55 mL (1.9 USoz)	55 mL (1.9 USoz)	55 mL (1.9 USoz)
Vibration level Cutting wood:	4.8 m/s ²	4.6 m/s ²	4.8 m/s ²
Dimensions (L x W x H)	w/o Battery: 408 x 90 x 232 mm (16 x 3-1/2 x 9-1/8") w/ BL1815N / BL1820B: 445 x 90 x 245 mm (17-1/2 x 3-1/2 x 9-5/8") w/ BL1830B / BL1840B / BL1850B / BL1860B: 459 x 90 x 249 mm (18 x 3-1/2 x 9-3/4")	w/o Battery: 357 x 90 x 232 mm (14 x 3-1/2 x 9-1/8") w/ BL1815N / BL1820B: 394 x 90 x 245 mm (15-1/2 x 3-1/2 x 9-5/8") w/ BL1830B / BL1840B / BL1850B / BL1860B: 408 x 90 x 249 mm (16 x 3-1/2 x 9-3/4")	w/o Battery: 350 x 90 x 215 mm (13-3/4 x 3-1/2 x 8-1/2") w/ BL1016/BL1021B: 383 x 90 x 220 mm (15-1/8 x 3-1/2 x 8-5/8") w/ BL1041B: 398 x 90 x 226 mm (15-5/8 x 3-1/2 x 8-7/8")
Net weight	1.7-2.0 kg (3.7-4.4 lbs.)	1.6-2.0 kg (3.5-4.4 lbs.)	1.5-1.6 kg (3.3-3.5 lbs.)

Standard Equipment: Saw chain, Guide bar, Guide bar case, Round file set (country-specific), Chain oil (country-specific), Battery, Charger

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table.

Items of standard equipment and specifications may vary by country or area.

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN 202307