

Accessories

End nozzle 74 set

Part No. 1914H0-2

A nozzle suitable for blowing away wet fallen leaves or other heavy objects.



Flat nozzle set

Part No. 1914H1-0

A nozzle for blowing off fallen leaves adhering to the ground, etc.



Portable Power Pack

Portable Power Pack

High energy capacity of 1,500Wh  
PDC1500

Charger

DC4001

Charging time

PDC1500: 450 min.



Energy capacity of 1,200Wh  
PDC1200

Charger

DC4001

Charging time

PDC1200: 360 min.



XPT

High water-resistance allows to operate the machine even if it is wet with water.



Battery Powered

Blower

UB003C



Grass Trimmer

UR101C

UR201C

UR202C



Backpack Blower

UB004C



Lawn mower

LM001C



Adapter set

40Vmax

Part No.

191N62-4



Adapter between  
Battery box of Portable  
power pack and  
Product on 40Vmax  
XGT platform

18Vx2

Part No.

191J51-5



Adapter between  
Battery box of Portable  
power pack and  
Product on 18Vx2 LXT  
platform

Charging Time

DC4001	
PDC1500	450 min
PDC1200	360 min

Battery Powered Backpack Blower

UB004C			
	Variable Speed	Air volume	w/ PDC1500, Cruise control mode, Mode 1 / 2 / 3: 8.5 / 15.2 / 19.7 m³/min w/ PDC1500, Boost mode: 20.9 m³/min
	Anti-restart function	Max air velocity	w/ PDC1500, Cruise control mode, Mode 1 / 2 / 3: 33.2 / 59.0 / 76.3 m/s w/ PDC1500, Boost mode: 80.7 m/s
	Electronic 3-Speed	Blowing force	w/ PDC1500, Cruise control mode, Mode 1 / 2 / 3: 5 / 15 / 25 N w/ PDC1500, Boost mode: 28 N
	Constant Speed	No load speed	Cruise control mode, Mode 1 / 2 / 3: 10,500 / 18,000 / 22,500 min⁻¹ Boost mode: 23,800 min⁻¹
Standard Equipment :		Continuous use (Attachment) (Battery)	55-200 min Standard nozzle PDC1500
		Vibration level	Operation w/o load, EN50636-2-100: 2.5 m/s² or less
		Vibration K factor	Operation w/o load, EN50636-2-100: 1.5 m/s²
		Sound pressure level	EN50636-2-100: 82.3 dB(A)
		Sound power level	EN50636-2-100: 96.1 dB(A)
End nozzle, Flat nozzle, Pipe support belt complete, Pipe belt complete		Noise K factor	3.1, 2.1 dB(A)
		Dimensions (L x W x H)	460 x 575 x 585 mm (18-1/8 x 22-5/8 x 23")
		Net weight	16.5 - 18.6 kg (36.4 - 41.0 lbs.)
		(Battery)	PDC1200 - PDC1500

Portable Power Pack

PDC1500	
Capacity	43.55 Ah
Energy capacity	1,567.8 Wh
Number of cells	130
Charging time	450 min.
Dimensions (L x W x H)	w/o Harness: 369 x 312 x 131 mm (14-1/2 x 12-1/4 x 5-1/8")
Net weight	Battery only: 10.9 kg (24.0 lbs.)* Harness assembly: 12.9 kg (28.4 lbs.)*
Power supply cord	Battery side: 1.2 m (3.9 ft) Adapter side: 0.6 m (2.0 ft)
*not covered by EPTA-Procedure	
Standard Equipment : Harness, Charger	

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table.  
Items of standard equipment and specifications may vary by country or area.

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan



PRINTED IN JAPAN 202404

www.makita.com



Battery Powered Backpack Blower  
UB004C  
Portable Power Pack  
PDC1500

Satisfy Professional's Needs



Max blowing force

Boost mode\*

28 N

With Standard nozzle / PDC1500

Max air volume

Boost mode\*

20.9 m³/min

Run time

Blowing force of 10N / Max blowing force

200 / 55 min

With Standard nozzle / PDC1500 / Cruise control lever

\*Max continuous use of Boost mode is 10 sec. After 10 sec. of use, the machine does not shift to Boost mode for 20 sec.

With End nozzle 74



With Flat nozzle







**High blowing force of 25N and Max blowing force of 28N in Boost mode (with a time limit)**



## High power

The airflow path from Fan has been changed from a curved line in Predecessor model to a straight line, increasing blowing efficiency by approx 10%.



Max blowing force  
Boost mode\*

**28 N**

Max air volume  
Boost mode\*

**20.9 m³/min**

Max air velocity  
Boost mode\*

**80.7 m/s**

With Standard nozzle / PDC1500

\*Max continuous use of Boost mode is 10 sec. After 10 sec. of use, the machine does not shift to Boost mode for 20 sec.



**Connector**

# High blower performance similar to 65 cm³ class engine backpack blower

**1,500Wh  
high capacity**

Portable Power Pack

**PDC1500**

**Quick removal/attachment**

allows for the battery to be easily removed or attached to the main unit.



**Reflectors**

keep operator visible from a distance even in the dark.



**4-LED fuel gauge**

indicates the battery status by four green LEDs.



**XPT**

**eXtreme Protection Technology /  
IPX4 compatible**

High water-resistance allows to operate the machine even if it is wet with water.



**Three speed  
mode button**



**Battery fuel gauge**

Three green LEDs



**Telescopic nozzle  
structure**

stepless adjustment



**Improvements for more comfortable  
backpacking experience**

Redesigned backpack harness section for more comfortable backpacking experience

- Mesh fabric for belts for improved breathability
- Shoulder belt material and shape have been redesigned to reduce the stress on user's shoulders



**Variable speed control by trigger +  
Cruise control lever**

- Trigger can be fixed at a desired position by user.
- The machine can shift to Boost mode by pulling Trigger fully from the position where Trigger stops in the halfway position.



**Position-adjustable grip**

The grip position is adjustable forward/backward and left/right to suit user's size or work posture.

