



## Cordless Trimmer DRT52 6mm(1/4")

Satisfy Professional's Needs

**LXT**



### Work amount

Cut Melapi (1m) with a ø6mm straight bit and at a cutting depth of 6mm

**about 105 m**

Battery: BL1860B  
on a full battery charge

**18V**  
**LITHIUM-ION**

**BL** **XPT**  
MOTOR

Brushless motor provides output efficiency similar or superior to that of our corded models.



**BL  
MOTOR**




**Lock/unlock button and Power button**

Lock/unlock button

LED lamp for indication of being unlocked

Power button



**Smooth and precision depth adjustment**

with rack and pinion mechanism



**Rubberized soft grip**

provides comfort and control



**Transparent plastic base**

for clear view of trimming edge



**XPT**

(eXtreme Protection Technology)

**Accessories**

**Trimmer base assembly set**

Transparent base

Part No. 194267-1\*

Standard equipment



\*With Fine depth adjustment

**Charging Time**

	Fast Charging DC18RC	DC18SD
<b>BL1815N</b> 1.5Ah 196449-1	<b>15 min</b>	<b>30 min</b>
<b>BL1820B</b> 2.0Ah 197254-9	<b>24 min</b>	<b>45 min</b>
<b>BL1830B</b> 3.0Ah 197599-5	<b>22 min</b>	<b>60 min</b>
<b>BL1850B</b> 5.0Ah 197280-8	<b>45 min</b>	<b>110 min</b>
<b>BL1860B</b> 6.0Ah 197422-4	<b>55 min</b>	<b>130 min</b>

**Cordless Trimmer**

**DRT52 6 mm (1/4")**



Soft Start



Anti-restart function

**Standard Equipment :**

Wrench, Templet guide, Chip deflector,  
Straight bit, Trimmer guide assembly,  
Straight guide assembly, Battery,  
Charger

Collet size	6 mm (1/4")
No load speed	30,000 min <sup>-1</sup>
Base shape	Square (82 x 90mm)
Base material	Plastic
Housing material	Plastic
Sound pressure level	81 dB(A)
Sound power level	89 dB(A)
Uncertainty (K)	3 dB(A)
Vibration level	Rotation w/o load: 2.5 m/s <sup>2</sup> or less
Uncertainty (K)	Rotation w/o load: 1.5 m/s <sup>2</sup>
Dimensions (L x W x H)	w/BL1860B: 134 x 90 x 220 mm (5-1/4 x 3-1/2 x 8-5/8")
Net weight	1.3 - 1.6 kg (2.9 - 3.5 lbs.)
Net weight (Battery)	BL1815N - BL1860B

The weight may differ depending on the attachment(s), including the battery cartridge.

The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table.

Items of standard equipment and specifications may vary by country or area.

**Makita Singapore Pte Ltd**

7, Changi South Street 3, Singapore 486348

Phone : +65-6546-8700 Fax : +65-6546-8711

Email : msgproductteam@makita.com.sg

Website : www.makita.com.sg

Facebook : www.facebook.com/MakitaSG



VISIT OUR WEBSITE



DOWNLOAD LEAFLET

PRINTED IN SINGAPORE