

SOCKET WRENCH

For manual

9.5

STAINLESS TOOL
TITANIUM TOOL

TOOL SET

TOOL CASE

SOCKET
WRENCH

HEXAGON
WRENCH

T-TYPE
WRENCH

SPANNER
OFFSET WRENCH

SCREWDRIVER

BIT

ADJUSTABLE
WRENCH
PLIERS

SPECIALIZED
CAR EQUIPMENT

CYCLE TOOL

LED LIGHT


OTHER HAND
TOOLS

TORQUE
WRENCH

AIR TOOL

Ball joint is used on complicated place.

Rotates very smoothly as the ball-shaped joint refracts only one time.




BJ30

BALL JOINT


Models	Square Drive (mm)	Dimensions (mm)				Qty./Carton		Weight (g)
		D ₁	D ₂	L ₁	L	(Generally)	(Store Center)	
BJ30	9.5	19	17.5	12	44	10	6	50

- Swing angle : About 30 degree



Universal joint is used on complicated place.

Angled work is available thorough connecting between the socket and the handle. Became more compact than before.




UJ30

UNIVERSAL JOINT

Models	Square Drive (mm)	Dimensions (mm)				Qty./Carton		Weight (g)
		D ₁	D ₂	L ₁	L	(Generally)	(Store Center)	
UJ30	9.5	19	19	11.5	43	10	6	54

- Swing angle : In left and right, 45 degree




CAUTION

- Strength of joints is about half of that of ratchet handle (JIS and ISO), because they are composed of output square drive and input square drive components and have poor power transmission rate. Do not handle joints roughly.

Universal joint is used on complicated place.

Angled work is available thorough connecting between the socket and the handle.




208

UNIVERSAL JOINT

Models	Square Drive (mm)	Dimensions (mm)				Qty./Carton		Weight (g)
		D ₁	D ₂	L ₁	L	(Generally)	(Store Center)	
★ 208	9.5	19	19	12.5	54	10	6	65

- ★ Require stock availability.


- Swing angle : In left and right, 75 degree



CAUTION

- Strength of joints is about half of that of ratchet handle (JIS and ISO), because they are composed of output square drive and input square drive components and have poor power transmission rate. Do not handle joints roughly.

Used to change drive size.



48

58


SOCKET ADAPTOR

Models	Square Drive (mm)	Dimensions (mm)			Qty./Carton		Weight (g)
		D	L ₁	L	(Generally)	(Store Center)	
※1 48	9.5 □ × 6.35 □	17.0	13	23.9	10	6	25
58	9.5 □ × 12.7 □	18.5	13	32.0	10	6	40



CAUTION

- Do not apply excessive force in case of adaptor (※1) having large concave sq. drive, as convex sq. drive might be broken.
- Limit-torque of adaptor is based in smaller sq. drive.



Use spinner handle as a T-type handle with crossbar.



CB30



CROSS BAR

Models	Dimensions (mm)		Qty./Carton		Weight (g)
	D	L	(Generally)	(Store Center)	
★ CB30	9	150	10	6	85

- ★ Require stock availability.



CAUTION

- Do not use with power tools.
- Do not assemble multiple attachments. (Extension bar, Universal joint, Socket adaptor, Quick adaptor)