



LONG IMPACT SOCKET (12pt.)

Models	Across Flat (mm)	Dimensions (mm)					Qty./Carton		Weight (g)
	S	D ₁	D ₂	L ₁	L	d	(Generally)	(Store Center)	
6NW-17L100	17	27.0	38	14	100	14	5	5	379
6NW-19L100	19	29.0	38	14	100	16	5	5	362
6NW-21L100	21	31.5	38	15	100	18	5	5	401
6NW-22L100	22	33.0	38	15	100	18	5	5	428
6NW-23L100	23	34.5	38	15	100	20	5	5	411
6NW-24L100	24	36.0	40	17	100	20	5	5	514
6NW-26L100	26	38.0	42	19	100	22	5	5	558
6NW-27L100	27	40.0	42	19	100	22	5	5	532
6NW-28L100	28	41.0	42	20	100	22	5	5	539
6NW-29L100	29	42.0	42	20	100	22	5	5	547
6NW-30L100	30	44.0	42	21	100	25	5	5	569
6NW-32L100	32	46.5	42	21	100	25	5	5	593
6NW-35L100	35	50.0	45	23	100	25	5	5	617
6NW-36L100	36	52.0	45	23	100	25	5	5	644
6NW-38L100	38	56.0	45	23	100	30	5	5	773
6NW-41L100	41	59.0	45	23	100	35	5	5	801
6NW-46L100	46	65.0	45	23	100	35	5	5	852

12-Point Strong Drive

※ This product is patent registered.

※ In case of out-of-stock, the impact socket will be automatically changed to double-grooved type.



Pin/O-ring compatible chart

Models	6NW-	17L100 ~ 46L100
Pin		P4033S
O-ring		RAS322S

※ Within a plastic bag (10 pcs./pkg.)

Long impact socket.
Electroless nickel plating.
Better appearance and anti-rust.



6NW-32L100



LONG IMPACT SOCKET (6pt.)

Models	Across Flat (mm)	Dimensions (mm)					Qty./Carton		Weight (g)
	S	D ₁	D ₂	L ₁	L	d	(Generally)	(Store Center)	
6NV-27L150	27	40.0	42	19	150	22	3	3	784
6NV-30L150	30	44.0	42	21	150	25	3	3	821
6NV-32L150	32	46.5	42	21	150	25	3	3	846
6NV-36L150	36	52.0	45	23	150	25	3	3	936
6NV-41L150	41	59.0	45	23	150	35	3	3	1,229
6NV-46L150	46	65.0	45	23	150	35	3	3	1,284
6NV-50L150	50	70.0	50	25	150	38	3	3	1,177

6-Point Strong Drive

※ This product is patent registered.

※ In case of out-of-stock, the impact socket will be automatically changed to double-grooved type.



Pin/O-ring compatible chart

Models	6NV-	27L150 ~ 50L150
Pin		P4033S
O-ring		RAS322S

※ Within a plastic bag (10 pcs./pkg.)

Super-long impact socket.
Electroless nickel plating.
Better appearance and anti-rust.



6NV-32L150



For impact wrenches

WARNING

- Use right size o-ring and pin securely fixed.
- O-ring and pin are consumptive parts. Replace those which are deteriorated or worn.

For impact

19.0

STAINLESS TOOL
TITANIUM TOOL

TOOL SET

TOOL CASE

SOCKET
WRENCH

HEXAGON
WRENCH

T-TYPE
WRENCH

SPANNER
OFFSET WRENCH

SCREWDRIVER

BIT

ADJUSTABLE
WRENCH
PLIERS

SPECIALIZED
CAR EQUIPMENT

CYCLE TOOL

LED LIGHT

OTHER HAND
TOOLS

TORQUE
WRENCH

AIR TOOL