

# SOCKET WRENCH

For impact

25.4

STAINLESS TOOL  
TITANIUM TOOL

TOOL SET

TOOL CASE

SOCKET  
WRENCH

HEXAGON  
WRENCH

T-TYPE  
WRENCH

SPANNER  
OFFSET WRENCH

SCREWDRIVER

BIT

ADJUSTABLE  
WRENCH  
PLIERS

SPECIALIZED  
CAR EQUIPMENT

CYCLE TOOL

LED LIGHT

OTHER HAND  
TOOLS

TORQUE  
WRENCH

AIR TOOL

Suitable for narrow, deep places as extending impact socket.  
Electroless nickel plating.  
Better appearance and anti-rust.



## ■ Pin/O-ring compatible chart

Models NE80-	150 ~ 400
Pin	P4040S
O-ring	RAS326S

※ Within a plastic bag (10 pcs./pkg.)

Angled work is possible with a connection between the socket and handle. Suitable for working on complicated space.  
Appearance and anti-rust upgraded with electroless nickel plating.



Model change




## ■ Pin/O-ring compatible chart

Models NJ	80
Pin	P4040S
O-ring	RAS326S

※ Within a plastic bag (10 pcs./pkg.)



<Example>



## ■ Pin/O-ring compatible chart

Models NJ	80S
Pin	P4040S
O-ring	RAS326S

※ Within a plastic bag (10 pcs./pkg.)

## ■ Repair kit Models RK-NJ80 NEW



Used to change drive size.  
Electroless nickel plating.  
Better appearance and anti-rust.



## ■ Pin/O-ring compatible chart

Models NA	86, 812
Pin	P4040S
O-ring	RAS326S

※ Within a plastic bag (10 pcs./pkg.)

## ⚠ CAUTION


- Do not apply excessive force in case of adaptor (※1) having large concave sq. drive, as convex sq. drive might be broken.
- Limit-torque of adaptor is based on smaller sq. drive.
- Do not assemble multiple attachments. (Extension bar, Universal joint, Socket adaptor, Quick adaptor)

## IMPACT EXTENSION BAR

Models	Square Drive (mm)	Dimensions (mm)					Qty./Carton		Weight (g)
		D	L <sub>1</sub>	L <sub>2</sub>	L	d	(Generally)	(Store Center)	
NE80-150	25.4	48	31	122	150	28	2	2	960
NE80-200	25.4	48	31	172	200	28	2	2	1,245
NE80-250	25.4	48	31	222	250	30	2	2	1,615
NE80-300	25.4	48	31	272	300	33	2	2	1,975
NE80-400	25.4	48	31	372	400	33	1	1	2,825

※ This product is patent registered.

※ In case of out-of-stock, the impact socket will be automatically changed to double-grooved type.




## IMPACT BALL JOINT

Models	Square Drive (mm)	Dimensions (mm)				Qty./Carton		Weight (g)
		D <sub>1</sub>	D <sub>2</sub>	L <sub>1</sub>	L	(Generally)	(Store Center)	
NJ80	25.4	55	48	31	138	2	2	1,320

● Swing angle : About 20 degree

※ This product is patent registered.

※ In case of out-of-stock, the impact socket will be automatically changed to double-grooved type.



## IMPACT BALL JOINT, SHORT TYPE

Models	Square Drive (mm)	Dimensions (mm)				Qty./Carton		Weight (g)
		D <sub>1</sub>	D <sub>2</sub>	L <sub>1</sub>	L	(Generally)	(Store Center)	
NJ80S	25.4	55	48	31	110	2	2	960

● Swing angle : About 20 degree

※ This product is patent registered.

※ In case of out-of-stock, the impact socket will be automatically changed to double-grooved type.



## ■ Repair kit Models RK-NJ80S NEW




## IMPACT SOCKET ADAPTOR

Models	Square Drive (mm)	Dimensions (mm)			Qty./Carton		Weight (g)
		D	L <sub>1</sub>	L	(Generally)	(Store Center)	
NA86	25.4 Concave x 19.0 Convex	48	31	62	5	5	380
NA812	25.4 Concave x 38.1 Convex	49	31	80	2	2	825

※ This product is patent registered.

※ In case of out-of-stock, the impact socket will be automatically changed to double-grooved type.



## ⚠ CAUTION

- Do not apply excessive force in case of adaptor (※1) having large concave sq. drive, as convex sq. drive might be broken.
- Limit-torque of adaptor is based on smaller sq. drive.
- Do not assemble multiple attachments. (Extension bar, Universal joint, Socket adaptor, Quick adaptor)

