


IMPACT SOCKET (12pt.)

Electroless nickel plating.
Better appearance and anti-rust.

Models	Across Flat (mm)	Dimensions (mm)						Qty./Carton (Generally)	Weight (kg)
	S	D ₁	D ₂	L ₁	L	d			
12AD-41	41	70	85	25	80	35	1	1	2.0
12AD-46	46	74	85	27	80	35	1	1	2.1
12AD-50	50	80	85	30	90	52	1	1	2.3
12AD-54	54	85	85	32	95	53	1	1	2.6
12AD-55	55	85	85	32	95	54	1	1	2.6
12AD-58	58	90	85	32	95	56	1	1	2.8
12AD-60	60	92	85	35	100	59	1	1	3.0
12AD-63	63	97	85	35	100	62	1	1	3.1
12AD-65	65	100	85	35	110	64	1	1	3.7
12AD-67	67	106	85	37	110	65	1	1	4.0
12AD-70	70	109	85	37	115	69	1	1	4.3
12AD-71	71	110	85	39	115	70	1	1	4.3
12AD-75	75	114	85	39	120	75	1	1	4.7
12AD-77	77	116	85	41	120	77	1	1	4.8
12AD-80	80	120	85	43	125	80	1	1	5.2
12AD-85	85	127	85	46	130	85	1	1	5.8
12AD-90	90	132	85	49	135	90	1	1	6.3
12AD-95	95	137	85	52	140	95	1	1	6.8
12AD-100	100	147	85	55	150	100	1	1	8.5
12AD-105	105	152	85	59	160	105	1	1	9.5
12AD-110	110	162	85	62	165	110	1	1	11.2
12AD-115	115	167	85	65	170	115	1	1	11.8
12AD-120	120	172	85	69	175	120	1	1	12.6

※ Usable with power wrench.



Pin/O-ring compatible chart

Models	12AD-	41 ~ 120
Pin		PIN7075
O-ring		RINGP75

※ Within a plastic bag (1 pcs./pkg.)


IMPACT SOCKET ADAPTOR

Used to change drive size.
Electroless nickel plating.
Better appearance and anti-rust.

Models	Square Drive (mm)	Dimensions (mm)			Qty./Carton		Weight (g)
		D	L ₁	L	(Generally)	(Store Center)	
NA128	38.1 Concave × 25.4 Convex	71	43	83.5	2	2	1,395

※ This product is patent registered.

※ In case of out-of-stock, the impact socket will be automatically changed to double-grooved type.



Pin/O-ring compatible chart

Models	NA	128
Pin		P4064
O-ring		RP60

※ Within a plastic bag (1 pcs./pkg.)

CAUTION

- Do not apply excessive force in case of adaptor having large concave sq. drive, as convex sq. drive might be broken.
- Limit-torque of adaptor is based on smaller sq. drive.
- Do not assemble multiple attachments. (Extension bar, Universal joint, Socket adaptor, Quick adaptor)



For impact wrenches

WARNING

- Use right size o-ring and pin securely fixed.
- O-ring and pin are consumptive parts. Replace those which are deteriorated or worn.



12AD-70



NA128

For impact

38.1

STAINLESS TOOL
TITANIUM TOOL

TOOL SET

TOOL CASE

SOCKET
WRENCH

HEXAGON
WRENCH

T-TYPE
WRENCH

SPANNER
OFFSET WRENCH

SCREWDRIVER

BIT

ADJUSTABLE
WRENCH
PLIERS

SPECIALIZED
CAR EQUIPMENT

CYCLE TOOL

LED LIGHT

OTHER HAND
TOOLS

TORQUE
WRENCH

AIR TOOL