


RING WRENCH, LONG TYPE

Most suitable for a working in confined space.
Easy to work on with 12-point head.

Models	Across Flat (mm)	Dimensions (mm)					Qty./Carton		Weight (g)
		D ₁	D ₂	T ₁	T ₂	L	(Generally)	(Store Center)	
M04-0810	8 × 10	13.5	16.0	7.5	8.0	184	10	10	50
M04-1012	10 × 12	16.0	18.5	8.5	9.0	192	10	10	70
M04-1113	11 × 13	17.0	19.0	9.0	9.5	193	10	10	75
M04-1214	12 × 14	18.5	21.0	9.5	10.0	224	10	10	105
M04-1315	13 × 15	19.0	23.0	9.5	11.0	240	10	10	120
M04-1417	14 × 17	21.0	25.5	11.0	12.0	252	10	10	135



CAUTION


- Avoid giving shock by hitting with hammer etc.



RING WRENCH, SHORT TYPE

Most suitable for a working in confined space.

Models	Across Flat (mm)	Dimensions (mm)					Qty./Carton		Weight (g)
		D ₁	D ₂	T ₁	T ₂	L	(Generally)	(Store Center)	
M03-0810	8 × 10	13.5	16.0	5.5	6.5	108	10	10	25
M03-1012	10 × 12	16.0	18.5	6.5	7.5	115	10	10	40
M03-1113	11 × 13	17.0	19.0	7.0	8.0	115	10	10	40
M03-1214	12 × 14	18.5	21.0	7.5	8.5	130	10	10	60
M03-1315	13 × 15	19.0	23.0	8.0	9.0	135	10	10	80
M03-1417	14 × 17	21.0	25.5	8.5	9.5	145	10	10	80



CAUTION


- Avoid giving shock by hitting with hammer etc.



STRIKING FACE RING SPANNER

Most suitable when hammer is required to tighten and loosen rusty bolt/nut!!

Models	Across Flat (mm)	Dimensions (mm)								Qty./Carton	Weight (g)
		S	D ₁	D ₂	T ₁	T ₂	L	L ₁	d ₁		
DM-36	36	58	35	19	11	205	18	11	5	5	615
DM-41	41	65	40	20	12	230	20	12	5	5	735
DM-46	46	74	41	22	13	240	20.5	12	5	5	965
DM-50	50	80	44	24	16	255	22	12	5	5	1,325
DM-55	55	86	48	25	15	270	24	14	5	5	1,415



Example



NEW



OFFSET WRENCH WITH WEDGE END

Models SMN-16, SMN-20, SMN-22, SMN-22S, SMN-30M, SMN-24



Turn to P335 for more information.

OFFSET WRENCH WITH WEDGE END

Models TSM-16, TSM-20, TSM-22



Turn to P335 for more information.

CAUTION

- Use wrench suitably fitted with bolt / nut.
- Do not bang tools except for striking face ring spanners.