

Slit socket ideal to used for various sensors with wiring cords and protrusions (TV valves, O₂ sensors, etc.).
Finished the knurling with quick turn.



3SLT-19



Example

Recommended socket set for work including drain bolt for car differential and manual gearbox. The set comes with drain plug socket with a square size of 10.5 and 13 mm, and a dual square socket (8pt.) with size of 17 mm.



4SQ-13

4SQ-10

4E-17

4pt (Square) socket ideal for drain plugs of the gearbox and differential gear. Useable by putting a wrench on the hexagonal (24 mm) part of the outer circumference.





4SQ-13

4SQ-10

SLIT SOCKET (6pt.)

Models	Across Flat (mm)	Dimensions (mm)			Qty./ Carton (Generally)	Weight (g)
		S	D	A		
3SLT-19	19	28	18	60	10	150
3SLT-22	22	32	40	100	10	310

- 6 Points strong drive



For TV valves (Vacuum connector) → Width across flats 19 mm
For O₂ sensor → Width across flats 22 mm

CAUTION

• Depending on car and engine model, sensor sockets and slit sockets may not be able to use.

DRAIN BOLT SOCKET SET

Models SQE403

Contents 3 Items

Descriptions	Models
DRAIN PLUG SOCKET	4SQ- 10, 13
DUAL SQUARE SOCKET (8pt.)	4E- 17




- Weight : 0.26kg

- Qty./Carton : 1



DRAIN PLUG SOCKET

Models	Across Flat (mm)	Dimensions (mm)					Qty./ Carton (Generally)	Weight (g)
		S	D	W	L ₁	L		
4SQ-10	10.5	27.0	24	8.0	29.0	10	10	76
4SQ-13	13	27.0	24	8.0	29.0	10	10	81



For tightening/loosening triple-squared socket head cap bolt (XZN) TRIPLE SQUARE (12P) SOCKET

Models 3TS-05, 3TS-06, 3TS-08, 3TS-10, 3TS-12, 3TS-14



Turn to P397 for more information.

