

Wheel nut socket (outer and inner) for large buses and trucks.
Easy to organize and get access to products with design case.



For bus/truck



A609T

STAINLESS TOOL
TITANIUM TOOL

TOOL SET

TOOL CASE

SOCKET
WRENCHHEXAGON
WRENCHT-TYPE
WRENCHSPANNER
OFFSET WRENCH

SCREWDRIVER

BIT

ADJUSTABLE
WRENCH
PLIERSSPECIALIZED
CAR EQUIPMENT

CYCLE TOOL

LED LIGHT

OTHER HAND
TOOLSTORQUE
WRENCH

AIR TOOL

Socket for tightening/loosening of outer nut for bus and truck.
Size can handle from medium-sized car to large car.



Outer nut



6A-41T

■ Pin/O-ring compatible chart

Models	6A-	30T ~ 35T	38T, 41T
Pin		PIN5039S	PIN5043S
O-ring		RINGW28S	RAS326S

※ Within a plastic bag (10 pcs./pkg.)

Socket for tightening/loosening of inner nut for bus and truck.
Size can handle from medium-sized car to large car.



Inner nut



6A-21BA

■ Pin/O-ring compatible chart

Models	6A-	17BA ~ 21BA	
Pin		P4033S	
O-ring		RAS322S	

※ Within a plastic bag (10 pcs./pkg.)

Socket for tightening/loosening of inner nut for bus and truck.
Size can handle from medium-sized car to large car.



Inner nut



6A-19B

■ Pin/O-ring compatible chart

Models	6A-	17B ~ 21B	
Pin		PIN5033S	
O-ring		RINGT32S	

※ Within a plastic bag (10 pcs./pkg.)

IMPACT SOCKET SET (for TRUCK WHEEL)

Models A609T


Contents 9 Items

Descriptions		Models	
BUDD WHEEL SOCKET (for OUTER NUT of TRUCK WHEEL)	6A-	32T, 33T, 35T, 38T, 41T	
BUDD WHEEL SOCKET (for INNER NUT of TRUCK WHEEL)	6A-	17B, 19B, 20B, 21B	
<ul style="list-style-type: none"> • 6 Points strong drive • For tightening/loosening outer nut and inner nut • Package size : w370x d160x h125mm • Weight : 6.3kg • Qty./Carton : 1 			

BUDD WHEEL SOCKET (for OUTER NUT of TRUCK WHEEL)

Models	Across Flat (mm)	Dimensions (mm)						Qty./Carton (Generally)	Weight (g)
		S	D ₁	D ₂	L ₁	L	d		
6A-30T	30	46	44	22	75	25	5	620	
6A-32T	32	48	44	22	75	25	5	650	
6A-33T	33	49	44	28	75	25	5	640	
6A-35T	35	50	44	28	75	25	5	630	
6A-38T	38	55	48	28	75	30	5	760	
6A-41T	41	58	48	28	75	35	5	755	

- 6 Points strong drive
- For tightening/loosening outer nut



CAUTION

- This thin-wall budd wheel socket is only for tire, please do not use on other applications.


BUDD WHEEL SOCKET (for INNER NUT of TRUCK WHEEL)

Models	Across Flat (mm)	Dimensions (mm)						Qty./Carton (Generally)	Weight (g)
		S	D ₁	D ₂	L ₁	L	d		
6A-17BA	17	38	38	20	55	5	355		
6A-19BA	19	40	38	20	55	5	375		
6A-20BA	20	41	38	20	55	5	385		
6A-21BA	21	42	38	20	55	5	395		

- For tightening/loosening inner nut



* This product is registered design.




CAUTION

- Hold square inner nut securely to use a budd wheel socket.

BUDD WHEEL SOCKET (for INNER NUT of TRUCK WHEEL)

Models	Across Flat (mm)	Dimensions (mm)						Qty./Carton (Generally)	Weight (g)
		S	D ₁	D ₂	L ₁	L	d		
6A-17B	17	38	38	21	66	27	5	5	365
6A-19B	19	38	38	21	66	28	5	5	340
6A-20B	20	38	38	21	66	31	5	5	315
6A-21B	21	40	38	21	66	31	5	5	340

- For tightening/loosening inner nut



CAUTION

- Hold square inner nut securely to use a budd wheel socket.



WARNING

- Use right size o-ring and pin securely fixed.
- O-ring and pin are consumptive parts. Replace those which are deteriorated or worn.