

TORQUE WRENCH, PRESET TYPE (DIGITAL READING • FOR BOTH OF R&L HAND THREADS)

Calibration Certificate Included

Test Report

Traceability Chart

Visible indicator that makes torque setting accurate and reduces wrong torque setting.

When preset torque has been reached, a click sound will occur with slight force from the wrench.

Left screw tightening is possible by inverting the torque wrench.



Visible Indicator
(Patent and design are already registered.)



Example



Models	Torque Range (N·m)	Increments	Units	Sq.dr A (mm)	Dimensions (mm)				Hand force at Max. torque (N)	Suitable bolt		Qty./Carton	Weight (kg)	Case Dimensions	
					B	H	T	L		Ordinary	High strength				
T4MN100R	20 ~ 100	1	N·m	12.7	36.0	49.2	14.0	387	335	M12 ~ M14	M10	1	0.83	480 × 78 × 49	
T4MN140R	30 ~ 140	1	N·m	12.7	36.0	49.2	14.0	450	388	M14	M10 ~ M12	1	0.88	480 × 78 × 49	
T4MN200R	40 ~ 200	2	N·m	12.7	45.2	52.7	20.5	526	474	M14 ~ M16	M12	1	1.42	625 × 78 × 59	
T6MN300R	40 ~ 300	2	N·m	19.0	45.2	65.2	20.5	716	441	M14 ~ M20	M12 ~ M14	1	1.96	795 × 105 × 80	


※ This product is registered design.

- N · m specification
- Torque Accuracy $\pm 3\%$

Accessory

Calibration Certificate W/H Traceability	1
Instruction Manual	1
Case	1

※ T4MN100R, T4MN140R and T4MN200R are leather cases.
T6MN300R is a metal case.



The minimum capacity range of T6MN300R has been expanded from 60N · m to 40N · m.

Expire Date of Calibration Certificate

- When not in use, the product can stay up to 3 years after calibration date mentioned in the certificate.
- If the usage started after 3 years from calibration date, it can be used up to 1 year since the first usage or up to 10,000 tightening times.

Repair · Maintenance

- Inaccuracy may occur if not used for a long time or inappropriate use of tool. Please contact your distributor regularly for accuracy check.
- Please contact your distributor in case of experiencing tool malfunction (no clicking sound, slight force, etc.)
- Torque devices require regular inspection (once a year or 10,000 times afterwards). Checking service is available with service charge.
- For more information about tool handling, please contact your distributor.
- Accuracy range after repair will be $\pm 4\%$.