



Hubs HUB2C

Ideal for use with computers, laptops, and Android mobile devices featuring USB Type-C ports and with iPad Pro, Transcend's HUB2C transforms a single USB Type-C port into four Type-A ones, instantly expanding the number of devices you can connect to your Type-C gadget at the same time. Connect accessories such as USB flash drives, keyboards, or mice to your tablet, or USB flash drives to your Android smartphone, and enjoy instant plug-and-play fun!



Reversible USB Type-C connector

Transcend's 4-port HUB2C comes with a reversible USB Type-C connector for greater ease of use. It is ideal for use with new laptops, Android smartphones, tablets and iPad Pro featuring a USB Type-C port.

*To view image or video files on your iPad Pro, name each file based on the DCF (Design rule for Camera File system) standard.



Transforms a single port into four

Ever wondered what to do with your Type-A products once you've gotten your hands on that new USB-C mobile device or laptop? Or, do you find the number of Type-C ports insufficient for all your devices? Equipped with the USB 3.1 Gen 1 interface, Transcend's HUB2C transforms a single Type-C port into four Type-A ones, instantly expanding the number of devices that you can connect to your device at one time.



An accessory to connect your life

Transcend's HUB2C allows you to connect accessories such as USB flash drives, keyboards, or mice to your tablet, or USB flash drives to your Android smartphone. Enjoy instant plug-and-play fun now!



Hubs HUB2C

Features

- USB 3.1 Gen 1 interface
- Supports devices with USB Type-C port
- Transfer seamlessly between old and new devices
- Slim and portable design
- Comes with 4 USB 3.1 Gen 1 ports and a USB Type-C cable attached

Specifications

Appearance

Dimensions	73.8 mm x 37.2 mm x 10.4 mm (2.91" x 1.46" x 0.41")
Weight	29 g (1.02 oz)

Interface

USB Type	USB Type-C
Input Interface	USB 3.1 Gen 1 USB Type-C
Output Interface	USB Type-A x4 (USB 3.1 Gen 1)
Connection Interface	USB 3.1 Gen 1

Operating Environment

Operating Temperature	0°C (32°F) ~ 70°C (158°F)
-----------------------	---------------------------

Power

Output Power	5V/0.9A from USB port
--------------	-----------------------

Warranty

Certificate	CE / FCC / BSMI / KC / RCM / EAC
-------------	----------------------------------

System Requirement

Operating System	Microsoft Windows 7 Microsoft Windows 8 Microsoft Windows 10 Mac OS X 10.2.8 or later Linux Kernel 2.6.30 or later iPadOS 13 or later
------------------	--

Ordering Information

OMB	TS-HUB2C
-----	----------

Product specifications are subject to change without notice. Pictures shown may differ from actual products. Total accessible capacity varies depending on operating environment.