





Transcend's 6-in-1 USB Type-C Hub HUB5C comes with a reversible USB Type-C connector equipped with the USB 3.1 Gen 2 interface to allow for amazing data transfer rates, a perfect complement to your new Type-C mobile, tablet, laptop, iPad Pro, or MacBook. Characterized by its easy expansion and plug-and-play functionality, the slim and lightweight Type-C hub boosts your work productivity without adding any burden. You can connect peripherals such as mice, keyboards, USB flash drives, external hard drives or portable SSDs, or take out the SD or microSD card as soon as you finish taking a photoshoot and read files directly from your laptop or mobile devices. Two Type-C ports allow you to charge your devices and transfer data at the same time, making everything twice as easy!



6-in-1 expansion

Transcend's 6-in-1 USB Type-C Hub expands the capabilities of your new Type-C mobile, tablet, laptop, MacBook or iPad Pro, featuring two USB-C ports for speedy pass-through charging and data transfer respectively, two USB-A ports, an SD card slot, and a microSD card slot. It is the first in the market to utilize the USB 3.1 Gen 2 interface in a Type-C connector, allowing for up to 10Gb/s amazing transfer rates.



Transfer data at next-generation speeds

Transcend's HUB5C is equipped with a USB Type-C port that utilizes the USB 3.1 Gen 2 interface to transfer data both ways at amazing 10Gb/s.*

*When tested with Transcend's ESD350C portable SSD, the port allows for data transfer rates at around 1000MB/s.



USB Power Delivery for 60W passthrough charging

The HUB5C comes with another Type-C port for 60W USB PD (Power Delivery) pass-through charging. You can connect your laptop manufacturer's charger to the USB PD port.

Note: 1. Type-C PD port is for charger only. The port does not support power output or data transfer.

2. Please click here for more details on USB PD pass-through charging.





Features

- USB 3.1 Gen 2 interface
- Perfect for Type-C mobiles, tablets, laptops, and new MacBooks
- 6-in-1 expansion
- USB PD 60W pass-through charging
- Supports SD and microSD cards

Specifications

Α	b	b	е	а	ra	n	се

Dimensions	103.5 mm x 44.9 mm x 12.3 mm (4.07" x 1.77" x 0.48")				
Weight	51 g (1.80 oz)				
Interface					
USB Type	USB Type-C				
Input Interface	USB 3.1 Gen 2 USB Type-C				
Output Interface	microSD Card Slot (UHS-I) SD Card Slot (UHS-II) USB Type-C (USB 3.1 Gen 2) USB Type-C (Max. 60W Power Delivery) USB Type-A x2 (USB 3.1 Gen 1)				
Connection Interface	USB 3.1 Gen 2				
Operating Environment					
Operating Temperature	0°C (32°F) ~ 50°C (122°F)				
Power					
Output Power	5V/0.9A from USB port Max. 20V/3A from Type-C port				
Input Power	5V/0.9A from USB port Max. 20V/3A from Type-C PD port				
Note	For a stable connection, the total power consumption of the devices connected to the hub must not exceed the stated output current.				
Warranty					
Certificate	CE / FCC / BSMI / KC / RCM / EAC / UKCA				
System Requirement					
Operating System	Microsoft Windows 7 or later macOS 10.2.8 or later iPadOS 13 or later Linux Kernel 2.6.30 or later				

Ordering Information

0MB	TS-HUB5C

Product specifications are subject to change without notice. Pictures shown may differ from actual products. Total accessible capacity varies depending on operating environment.