



2.5" SSDs

SATA III 6Gb/s SSD220S

Transcend's SATA III 6Gb/s SSD220S uses the latest 3D NAND technology that features vertical, stacked expansion of storage cells. By using high-quality flash memory and enhanced firmware algorithms, the SSD220S delivers greater performance and reliability.



3D expansion to break through limits

Unlike planar NAND memory, 3D NAND flash features memory cells stacked vertically in multiple layers. 3D NAND overcomes density limitations of 2D planar NAND, and delivers a higher level of performance and endurance.




Performance boost for everyday computing

Taking full advantage of the SATA III 6Gb/s interface and built-in SLC caching technology, Transcend's SSD220S achieves exceptional transfer speeds of up to 550MB/s read and 500MB/s write.



Guaranteed endurance and reliability

Transcend's SSD220S offers great Terabytes Written (TBW) values (up to 320 TB) indicating the total amount of data you can write into the drive over its lifetime.



2.5" SSDs

SATA III 6Gb/s SSD220S

Features

- 3D NAND flash
- Engineered with a RAID engine and LDPC (Low-Density Parity Check) coding to ensure data integrity
- Built-in SLC caching technology for exceptional transfer speeds
- Supports DevSleep ultra low power state, S.M.A.R.T., TRIM, and NCQ commands



SSD Scope

SSD Scope features useful functions to maintain your SSD in a healthy status and also copy data from your original HDD to Transcend's new SSD.

Specifications

Appearance

| | |
|------------|--|
| Dimensions | 100 mm x 69.85 mm x 6.8 mm (3.94" x 2.75" x 0.28") |
| Weight | 45 g (1.59 oz) |

Interface

| | |
|---------------|----------------|
| Bus Interface | SATA III 6Gb/s |
|---------------|----------------|

Storage

| | |
|------------|-----------------------------------|
| Flash Type | 3D NAND flash |
| Capacity | 120 GB / 240 GB / 480 GB / 960 GB |

Operating Environment

| | |
|-----------------------|---------------------------|
| Operating Temperature | 0°C (32°F) ~ 70°C (158°F) |
| Operating Voltage | 5V±5% |

Performance

| | |
|---|---|
| Sequential Read/Write (CrystalDiskMark) | Read: up to 550 MB/s Write: up to 500 MB/s |
| 4K Random Read/Write (IOMeter) | Read: up to 55,000 IOPS Write: up to 75,000 IOPS |
| Mean Time Between Failures (MTBF) | 2,000,000 hour(s) |
| Drive Writes Per Day (DWPD) | 0.3 (3 yrs) |
| Terabytes Written (TBW) | up to 320 TBW |
| Note | Speed may vary due to host hardware, software, usage, and storage capacity. The workload used to rate DWPD may be different from your actual workload, which may vary due to host hardware, software, usage, and storage capacity. Terabytes Written (TBW) expresses the endurance under the highest capacity. For Mac users please visit our Apple Solutions here . |

Warranty

| | |
|-------------|-----------------------------|
| Certificate | CE / FCC / BSMI / KC / RCM |
| Warranty | Three-year Limited Warranty |

Ordering Information

| | |
|-------|---------------|
| 120GB | TS120GSSD220S |
| 240GB | TS240GSSD220S |
| 480GB | TS480GSSD220S |
| 960GB | TS960GSSD220S |