Approved	Confirmed	Issued by
moel S	Moys	25 mml
(Mod)	(moy)	25mm

PRODUCT SPECFICATIONS

Style Number: KT-4410 (Kevlar KD)

1. Feature:

Kevlar and HDPE fiber knitted glove

2. Cut Level:

5

3. Applications:

Automotive, Sheet-Metal,/Iron Handing, Grinding, Welding,

Paper processing, Bottling, Cutting/Slicing Operations

4. Name, Color and Size

Name:

Kevlar KD

Color:

Yellow/White

Size:

Free size

5. Measurement (mm.)

Size	Free Size
1.Full length	225±10
2.Width of palm	105±5
3.Length of middle finger	85±5
4.Color of over lock	Yellow



6. Quality:

6.1 Appearances:

The glove should be well proportioned and comply with the following requirements.

- 6.1.1 The knitted cuff of shell should not be frayed.
- 6.1.2 Rubber sheet should be totally and firmly adhered onto the palm of the shell, and any spot being come off or exfoliated should not be observed.
- 6.1.3 The surface of the rubber should be glossy, and neither blooming nor frosting should be observed on the surface.
- 6.1.4 Any cut, crack, winkle, air bubble, and/or mixed alien substance should not be observed on the rubber.
- 6.1.5 Any speckle, stain, obscure embossed part should not be apparently observed on the rubber.
- 6.1.6 The rubber incorporated into the cuff should not be loose due to the heat during curing the rubber coated on the palm.

7. Appearance check on individual packaging:

7.1 Packing method:

7.1.1 : Individual Packing: Each pair of gloves shall be packed in a laminated bag.

7.2 Packing Quantity: 240 pairs per carton. Or as requested.

Ĭtems	Requirements	
Pairing gloves for packing	One-sided pairing is not allowed	
Tear on an individual package	No tear should be observed	
Stapling	Gloves should not be stapled.	
Sealing	An individual package should be neatly sealed.	